



Centrifugal Vegetable Drying Machine, Model: HS-ES

<https://www.jegerings.com/en/>



Advantages

- Stainless steel centrifugal vegetable dryer to remove the washing water.
- High quality and stable machine for industrial use.
- Operating principle: washed vegetables flow from the washing machine into special plastic baskets. The basket is placed in a special basket holder in the drying machine. After closing the lid the machine start automatically and running at the ideal speed (700 RPM) so that only the washing water gets removed while the product juices are maintained. Moreover, the product will not get damaged.
- After opening the lid, the machine stops immediately (brake motor) and the basket can be taken out of the machine. Optionally, an electronic timer can be installed to stop the HS-ES at a pre-set time.
- The HS-ES stands on four heavy levelers with vibration dampers, absorbing vibrations and keeping the machine in its place. Therefore it is not necessary to fix the machine to the floor.



Technical data and dimensional diagram

Dimensions: WxDxH = 580 x 830 x 970 mm, deployment altitude = 830 mm

Electrical data: 3 Ph / 400 V / 2.6 A / 2800 RPM, basket holder 700 RPM

Machine weight: 225 kg

The dimensional diagram of the HS-ES is shown on page 4.

Prices

Type HS-ES: on request

- Surcharge extra blue plastic drying baskets: on request
- Surcharge dense basket inserts (for small cut vegetables): on request
- Surcharge timer: on request

Delivery time: stock – 2 weeks

Delivery: ex. works Deurne/ the Netherland. Packaging and transportation excluded.

Guarantee: 1 year. Outside the Netherlands only spare parts.



